


SF-330

Auto Feed Pouch Laminator



SF-330
video



SF-330

Product Introduction

The new Sunfung fully automatic pouch laminator SF-330 is the next generation of sheet-fed, auto-trimming lamination technology with corner rounder. With a push of a button, it's easy to automatically feed, laminate and trim a stack of sheets with corner rounder in one pass. The SF-330 boasts a maximum laminating speed of 6m/min and can process up to 3000 photos(3 inch) per hour with a 4-side trim and corner round function that can alternate between no margin (flush-cut) and margin (encapsulated).

The sheet feeder for the SF-330 holds up to 300 sheets at a time, with a minimum sheet size of 63mm x 89mm, a maximum sheet width of 330mm and a long size for 700mm max. The feeder will accept paper weights ranging from 80gsm to 300gsm, with built in skew adjustment and adjustable resist roller pressure to prevent multi-sheet feeds over a wide range of paper stocks. All digital adjustments can be made using the easy-to-use touch screen panel, with temperature controls ranging from 60 to 150 degree and a quick warm-up time of 10 minutes.



What really sets this machine apart is its No Waste feature, which produces ZERO trim waste between encapsulated sheets. Even with sheets that are flush-cut, the unique engineering of the Revo Flex reduces trim waste by 70% compared to other automatic laminating systems. This significant reduction in trim waste translates to thousands of dollars saved in lamination costs over the lifetime of the SF-330. Lamination film rolls for the SF-330 come in 330mm widths and are currently available in 1.5mil, 3mil and 5mil thicknesses in gloss and matte finishes.

SF-330

Auto Feed Pouch Laminator

Main Feature

- Double side lamination with 4 side trimming
- Corner rounder include for good looking
- 6 m/min max laminating speed
- Bottom auto feeding method
- Easy to use 7 inch touch screen
- Zero trim waste
- 300 sheets feeding capacity
- Programmable set
- CE safety standard



Application



Technical Parameters

| Model | SF-330 |
|---------------------------|-------------------------------|
| Max laminating width | 330mm |
| Paper thickness | 80-300gsm |
| Paper size | 63x89mm to 330x700mm |
| Lamination | Double side |
| Trimming | 4 side |
| Corner round | Yes |
| Max laminating thickness | 0.5mm included paper and film |
| Laminating film thickness | 1.5, 3, 5mil |
| Film type | Gloss, Matte |
| Operation | 7 inch touch screen |
| Laminating speed | 1 - 6 m/min |
| Temperature | 60 - 150 degree adjustable |
| Warm up time | 10 minutes |
| Feed tray capacity | 300 sheets |
| Power | 220-240V, 50-60Hz |
| Consumption | 3000W |
| Weight | 190Kg |
| Package size | 1000x950x1600mm |