

SF-390/540

Semi-auto Laminator




SF-390
Video

Product Introduction

Introducing Sunfung's SF-390 and SF-540 Laminator Foiling: Elevating standard print projects to 'extraordinary' heights. The Sunfung SF-390 and SF-540 has been engineered to address specific print finishing needs and constructed to the highest technical standards – featuring fully adjustable pressure and heat settings, designed to provide optimal results with today's digital print outputs.



SF-390/540



Main Feature

- Semi-auto feeding with overlap feature
- Pneumatic auto separation
- The anti-curl bar allows thin film laminates to be flat
- Mirror chrome heating roller
- Thermal or Cold laminating
- Touch screen display system
- Digital foiling
- 2 rolls film installation
- Adjustable electric hydraulic pressure system



SF-540
Video

Technical Parameters

Model	SF-390	SF-540
Max laminate width	390mm	540mm
Laminate paper	157-350gsm	157-350gsm
Max speed	15 meters/min	15 meters/min
Control system	Hydraulic	Hydraulic
Max temperature	140 degree	140 degree
Heating mode	Oil heating	Oil heating
Upper roll	High gloss chromium plating 120mm	High gloss chromium plating 160mm
Down roll	Silicon rubber 80mm	Silicon rubber 100mm
Display	Touch screen	Touch screen
Motor	AC motor	AC motor
Input power	3500W	4000W
Paper overlap accuracy	1.5mm	1.5mm
Power	220V - 240V, 50-60Hz	220V - 240V, 50-60Hz
Core size	3 inch	3 inch
Film thickness	25 - 32 mic	17 - 42 mic
Package dimensions	760x830x1350mm	720x910x1360mm
Net weight	210Kg	240Kg
Gross weight	285Kg	325Kg